


## OPERATOR'S MANUAL

(Handbuch)

- O JAMMA STANDARD
- O MONITOR VERTICAL
- O POWER CONSUMPTION +5 V......5A +12 V....1A
- \* The Power shall be exactly +5V (Die Spannung muß 5,0 V sein!)

CONTROL PANEL (Spielpult)













## RAIDEN II - DIP SWITCH

DIP-#1  COIN 1 (3) (Coin / Credit)	Coin/Credits 1/1 1/2 1/3 1/4 2/1 3/1	ON OFF OFF ON ON	OFF OFF ON OFF ON	OFF OFF ON OFF ON	4	5	6	7	8	
Free play, if	4/1 1-8 ON!		ON							
COIN 2 (4) (Coin / Credit)  Free play. if	1/1 1/2 1/3 1/4 2/1 3/1 4/1 1-8 ON!				OFF ON OFF ON ON OFF		OF OF OF OF OF	FFVFVV		
COINS TO START GAME	Normal Double				a				OFF ON	
SCREEN FLIP	Normal Flip									OFF ON

## ATTENTION:

- A) Removal or alteration of Serial Number voids WARRANTY!
- B) Do NEVER remove or short the battery or it's connector! This will cause program-loss!

## (ACHTUNG:

- a) Das Entfernen oder die Veränderung der Serien-Nummer vernichtet GARANTIE!
- b) Niemals Batterie Kurzschließen oder Entfernen! Programm-Verlust ist die Folge!)

RAIDEN II

28-pin Connector

	Γ	SOLDER SIDE	No.	No.	PARTS SIDE
	ŀ	GND	A	1	GND
		GND	В	2	GND
		+5V	С	3	+5V
		+5V	D	4	+5V
	A		E	5	****
	W	+12V	F	6	+12V
	ŀ		Н	7	
		COUNTER 2	I	8	COUNTER 1
		~~~~~~~~~~~~~~~~~	K	9	****
		SPEAKER (-)	L	10	SPEAKER (+)
9	DIP 2		M	11	e o u o e o e o <del>e o e</del> u e u e e e e e e e e e e e e e e e
		GREEN	N	12	RED
	DIP 1	SYNC	P	13	BLUE
		SERVICE	R	14	VIDEO GND
			S	15	
		COIN 2	T	16	COIN 1
		2P START	U	17	1P START
		2P UP	V	18	1P UP
		2P DOWN	W	19	1P DOWN
		2P LEFT	X	20	1P LEFT
	l l	2P RIGHT	Y	21	1P RIGHT
		2P PUSH 1	Z	22	1P PUSH 1
		2P PUSH 2	a	23	· 1P PUSH 2
			b	24	
			С	25	
			d	26	
		GND	е.	27	GND
		GND	f	28	GND